

CANNON LOAD BANKS, INC.

PALMETTO, GA. 30268

PHONE 770-463-0504

MODEL L-10T PORTABLE LOAD BANK

The L-10T LOAD BANK is designed to provide a load for field servicing and testing 12V, 24V, 36V, and 48V DC motive batteries and power supplies. It is air cooled and completely self contained. There are four load steps for 12 and 24 volts. These can be combined for a total of 15 load steps. There are three steps for 36 and 48 volts. These can be combined for a total of 7 load steps.



MODEL L-10T DIMENSIONS

Length..... 22"
Width.....8"
Height.....11"
Weight.....40 lbs.



FEATURES

LOAD STEPS	12VDC	24VDC	36VDC	48VDC
1	15A	30A	45A	60A
2	25A	50A	75A	100A
3	50A	100A	150A	200A
4	100A	200A		
TOTAL AMPS	190A	380A	270A	360A

STEPS CAN BE COMBINED FOR 15 DIFFERENT LOADS AT 12 OR 24VDC OR STEPS CAN BE COMBINED FOR 7 DIFFERENT LOADS AT 36 AND 48VDC.

- Plug test pins for connecting test leads
- Meters: 0-50V voltmeter, 0-400A ammeter
- Power indicator light
- Thermal protection
- Carrying case