

CANNON LOAD BANKS, INC.

PALMETTO, GA. 30268

PHONE 770-463-0504

MODEL L-69-57

PORTABLE LOAD BANK

The L-69-57 LOAD BANK is designed to provide a temporary load for field servicing and testing 480VAC and 208VAC three phase, 60HZ generators and inverters. The L-69-57 load bank is air cooled. A 120VAC outlet is required to operate the fans and relays. The load is 57KW at 480VAC and 240 three phase. At 208VAC the unit will pull a load 45KW. This unit will also test 120VAC & 240VAC single phase.



MODEL L-69-57 DIMENSIONS

Length.....22"
Width.....8"
Height.....21"
Weight.....60 lbs.



FEATURES

- Load steps: 1, 2, 2, 5, 10, 12.5, 25 KW on three phase 480VAC and 240VAC
- Load steps: .8, 1.6, 1.6, 4, 8, 9.7, 19.3 KW on three phase 208VAC
- Load steps: 500W, 1KW, 1KW, 2.5KW, 5KW, 6.25KW, 12.5KW on single phase 240VAC
- Load steps: 130W, 250W, 250W, 630W, 1.25 KW, 1.5KW, 3KW on single phase 120VAC
- Tests 240VAC three phase, 240VAC single phase and 120VAC single phase
- Plug test pins for connecting test leads
- Receptacle for ten foot cable(included with load bank)
- Meters: 0-600V voltmeter, 0-150A ammeter, 55-65HZ frequency meter
- Power indicator lights
- Thermal protection
- Carrying case

WEBSITE: WWW.CANNONLOADBANKS.COM